


Axpert VM III TWIN IP52 Dust & Moisture Resistant Smart Inverter

OFF-GRID INVERTER




LCD Display Panel



• Detachable LCD control module with various communications

New control module and bottom case is integrated into a single design, making it easier to remove control module from main body of the inverter.



• Dual outputs for smart load management

There are two outputs available. The second output can be scheduled on/off, setting cut-off voltage or SOC and discharging time via LCD setting. It facilitates users smart load control.

• Super high PV input capacity at 40A – ready for modern solar panels

With a maximum PV input current of 40 A, the Axpert VM III TWIN IP52 meets the growing market demand for solar panels with increased Imp, ensuring seamless integration and optimal performance.

• Over-the-Air firmware upgrade-able by APP

Axpert VM III TWIN IP52 is integrated WiFi interface ready for mobile monitoring. With convenient mobile WiFi monitoring and Over-The-Air (OTA) firmware upgrades, users can effortlessly stay connected to their power system, monitor its performance, and seamlessly upgrade to the latest firmware for enhanced functionality and compatibility.




• BMS communication ready

Axpert VM III TWIN IP52 is built-in with BMS communication ports, allowing it to exchange real-time data, optimizing battery charging and discharging, maximizing efficiency, and enhancing safety.

• New thermal ventilation design with reduced noise level

Full-line convection cooling with few fans increases cooling efficiency. Moreover, depending on the temperature, the internal fans can be turned on appropriately to effectively reduce machine noise.




• Powerful Integration, Zero Internal Wiring

Axpert VM III TWIN IP52 combines advanced DSP control with a fully integrated circuit design—no internal wiring required. This innovation simplifies after-sales service time by 80%, delivering unmatched efficiency and reliability.

• Anti-Dust & Anti-Moisture Coating for Long-Lasting Reliability

A protective adhesive layer shields all electronic components from dust & moisture, enhancing durability and ensuring consistent performance over time.



• Ultra-Low No-Load Consumption

The Axpert VM3 IP52 cuts no-load current by 50%, lowering energy loss to under 1A for improved efficiency.

• New generation DSP

The new generation of DSPs offers a 50% increase in performance

• Flexibility for neutral/ground bonding

This feature provides more flexibility to suite diverse applications.

• Optional HMI remote box

An HMI remote box is available as an optional alternative for this series.

Axpert VM III TWIN IP52 Off-Grid Inverter Selection Guide

MODEL	Axpert VM III TWIN IP52 4.5K	Axpert VM III TWIN IP52 6.5K
Rated Power	4500VA/4500W	6500VA/6500W
INPUT		
Voltage	230 VAC	
Selectable Voltage Range	170-280 VAC (For Personal Computers) 90-280 VAC (For Home Appliances)	
Frequency Range	50 Hz/60 Hz (Auto sensing)	
OUTPUT		
AC Voltage Regulation (Batt. Mode)	230VAC ± 5%	
Surge Power	9000VA	13000VA
Efficiency (Peak)	93%	
Transfer Time	10 ms (For Personal Computers) 20 ms (For Home Appliances)	
Waveform	Pure sine wave	
BATTERY		
Battery Voltage	24 VDC	48 VDC
Floating Charge Voltage	27 VDC	54 VDC
Overcharge Protection	33 VDC	63 VDC
SOLAR CHARGER & AC CHARGER		
Solar Charger type	MPPT	
Maximum PV Array Power	6000W	9000W
MPP Range @ Operating Voltage	60 ~ 450 VDC	
Maximum PV Array Open Circuit Voltage	500 VDC	
Maximum PV Input Current	40A	40A
Maximum Solar Charge Current	120A	
Maximum AC Charge Current	100A	
Maximum Charge Current	120A	
PHYSICAL		
Dimension, D x W x H (mm)	400 x 300 x 115	
Net Weight (kgs)	9	10
Communication Interface	USB/RS232/RS485/WiFi/Dry-contact	
Ingress Protection	IP52	
OPERATING ENVIRONMENT		
Humidity	5% to 95% Relative Humidity (Non-condensing)	
Operating Temperature	-10°C to 50°C	
Storage Temperature	-15°C to 60°C	

Product specifications are subject to change without further notice.