

- 

MODEL	InfiniSolar WP HB 10kw
MAXIMUM PV INPUT POWER	14500W
RATED OUTPUT POWER	10000 W
MAXIMUM CHARGING POWER	10000 W
GRID-TIE OPERATION	
PV INPUT (DC)	
Nominal DC Voltage / Maximum DC Voltage	720 VDC / 900 VDC
Start-up Voltage / Initial Feeding Voltage	320 VDC / 350 VDC
MPP Voltage Range	350 VDC ~ 900 VDC
Number of MPP Trackers / Maximum Input Current	2 / A: 18A, B: 18A
Number of Strings Per MPP Tracker	A: 2, B: 2
GRID OUTPUT (AC)	
Nominal Output Voltage	230 VAC (P-N) / 400 VAC (P-P)
Output Voltage Range	184 - 265 VAC per phase
Nominal Output Current	14.5 A per phase
Power Factor range	0.9 lag ~ 0.9 lead
EFFICIENCY	
Maximum Conversion Efficiency (DC/AC)	>96%
European Efficiency@ Vnominal	>95%
OFF-GRID OPERATION	
AC INPUT	
AC Start-up Voltage / Auto Restart Voltage	120 - 140 VAC / 180 VAC
Acceptable Input Voltage Range	170 - 280 VAC per phase
Maximum AC Input Current	20 A
PV INPUT (DC)	
Maximum DC Power	14500 W
Maximum DC Voltage	900 VDC
MPP Voltage Range	350 VDC ~ 900 VDC
Number of MPP Trackers / Maximum Input Current	2 / A: 18A, B: 18A
Number of Strings Per MPP Tracker	A: 2, B: 2
BATTERY MODE OUTPUT (AC)	
Nominal Output Voltage	230 VAC (P-N) / 400 VAC (P-P)
Output Waveform	Pure sine wave
Efficiency (DC to AC)	94%
HYBRID OPERATION	
PV INPUT (DC)	
Maximum DC Voltage	720 VDC
Start-up Voltage / Initial Feeding Voltage	320 VDC / 350 VDC
MPP Voltage Range	350 VDC ~ 900 VDC
Number of MPP Trackers / Maximum Input Current	2 / A: 18A, B: 18A
Number of Strings Per MPP Tracker	A: 2, B: 2
GRID OUTPUT (AC)	
Nominal Output Voltage	230 VAC (P-N) / 400 VAC (P-P)
Output Voltage Range	184 - 265 VAC per phase
Nominal Output Current	14.5 A per phase
AC INPUT	
AC Start-up Voltage / Auto Restart Voltage	120 - 140 VAC / 180 VAC
Acceptable Input Voltage Range	170 - 280 VAC per phase
Maximum AC Input Current	20 A
BATTERY MODE OUTPUT (AC)	
Nominal Output Voltage	230 VAC (P-N) / 400 VAC (P-P)
Efficiency (DC to AC)	94%
BATTERY & CHARGER	
Battery Voltage Range	204 ~ 408 VDC
Maximum Charging Current	30 A
GENERAL	
PHYSICAL	
Dimension, D x W x H (mm)	255 x 660 x 600
Net Weight (kgs)	45
IP protection	IP65
INTERFACE	
Communication Port	RS-232, RS-485, USB, CAN and Wi-Fi
Intelligent Slot	Optional for SNMP and Modbus cards
ENVIRONMENT	
Humidity	0 ~ 100% RH (Non-condensing)
Operating Temperature	-25 to 60°C, > 45°C power derating
Altitude	0 ~ 1000 m**

** Power derating 1% every 100 m when altitude is over 1000m
Product specifications are subject to change without further notice.